

Appendix A


Shutesbury Public Library Site Plans

Shutesbury Public Library

66 Leverett Road, Shutesbury, MA 01072



PERMIT SET DECEMBER 21, 2023



OUDENS ELLO ARCHITECTURE, LLC

46 WALTHAM STREET, SUITE 4A BOSTON, MA 02118 T. 617.422.0980



CIVIL ENGINEER

FUSS & C'NEILL, INC. 1550 MAIN STREET, SUITE 400 SPRINGFIELE, MA 01103 T: 413.452.0445

LANDSCAPE ARCHITECT

STIMPSON 288 NORFOLK ST. CAMBRIDGE, MA 02139 T: 617.876.8960

STRUCTURAL ENGINEER

LEMESSURIER 1380 SOLDIERS FIELD RD. BOSTON, AM 02135 T: 617.868.1200

MEP/FP ENGINEER

BALA CONSULTING ENGINEERS 52 TEMPLE PLACE BOSTON, MA 02111 T: 617.357.6060

CODE/LIFE SAFETY

CODE RED CONSULTANTS 154 TURNPIKE RD., SUITE 200 SOUTHBOROUGH, MA 01772 T: 617.500.7633

SPECIFICATIONS

KALIN ASSOCIATES 1121 WASHINGTON ST. NEWTON, MA 02465 T: 617.964.5477

LIGHTING

LAM PARTNERS, INC. 84 Sherman Street Cambridge, MA 02140 T: 617.354.4502

ACOUSTICS

ACENTECH 33 MOULTON ST CAMBRIDGE, MA 02138 T: 617.499.8000

SOLAR DESIGN

SOLAR DESIGN ASSOCIATES 280 Ayer Rd, HARVARD, MA 01451 T: 978.456.6855

CODE CONSULTANTS

CODE RED CONSULTANTS 154 TURNPIKE ROAD, SUIT 200 SOUTHBOROUGH MA 01772 T. 617.500.7633

OWNER


TOWN OF SHUTSBURY 1 COOLEYVILLE RD. SHUTESBURY MA 01072-0276 T: 413.259.1214

OWNER'S PROJECT MANAGER

CONSTRUCTION MONITORING SERVICES 270 MAIN STREET MARLBOROUGH, MA 01752 T: 508.786.0600

SHEET INDEX

SHEET No.	SHEET TITLE
	COVER SHEET
C1.0	EXISTING CONDITIONS
C2.0	SITE PREPARATION PLAN
C3.0	SITE GRADING & DRAINAGE PLAN
C4.0	SITE UTILITY PLAN
C5.0	PAVEMENT MARKING & SIGN PLAN
C6.0	CONSTRUCTION DETAILS
C6.1	CONSTRUCTION DETAILS
C6.2	CONSTRUCTION DETAILS
C6.3	CONSTRUCTION DETAILS
L2.0	LAYOUT AND MATERIALS PLAN
L3.0	PLANTING PLAN
L3.1	PLANTING DETAILS
L4.0	SITE DETAILS





FUSS&O'NEILL

.8960 .6060 .4675 .1200 .4502

. 617.876.8 . 617.357.0 . 617.282. . 617.868. . 617.354.4 \vdash \vdash \vdash \vdash \vdash \vdash

100% SD Redesign Set 07.12.2023






FUSS&O'NEILL

617.8 617.8 617.8 617.8 617.8 \vdash \vdash \vdash \vdash \vdash \vdash


100% SD Redesign Set 07.12.2023



FUSS&O'NEILL


T. 617.876.8960 T. 617.357.6060 T. 617.282.4675 T. 617.868.1200 T. 617.354.4502 T. 781.749.7272

04.28.2023 100% SD Redesign Set 07.12.2023



- 1. EROSION AND SEDIMENT CONTROL MEASURES WILL BE INSTALLED PRIOR TO STUMP REMOVAL AND CONSTRUCTION. STABILIZATION OF ALL REGRADED AND SOIL STOCKPILE AREAS WILL BE INITIATED AND MAINTAINED DURING ALL PHASES
- 2. SEDIMENT REMOVED FROM EROSION CONTROL STRUCTURES WILL BE DISPOSED OF IN A MANNER WHICH IS CONSISTENT WITH THE INTENT OF THIS PLAN. ALL STRAW WATTLES OR SILT FENCE RETAINING SEDIMENT OVER 6" HIGH SHALL HAVE THE SEDIMENT REMOVED AND ALL DAMAGED EROSION CONTROLS REMOVED AND REPLACED. 3. THE CONTRACTOR WILL BE ASSIGNED THE RESPONSIBILITY FOR IMPLEMENTING THIS EROSION AND SEDIMENT CONTROL PLAN. THIS RESPONSIBILITY INCLUDES THE INSTALLATION AND MAINTENANCE OF CONTROL MEASURES, INFORMING ALL PARTIES ENGAGED ON THE CONSTRUCTION SITE OF THE REQUIREMENTS AND OBJECTIVES OF THE PLAN, AND NOTIFYING THE PROPER TOWN AGENCY OF ANY TRANSFER OF THIS RESPONSIBILITY. THE OWNER SHALL BE RESPONSIBLE FOR CONVEYING A COPY OF THE EROSION AND SEDIMENT CONTROL PLAN IF THE TITLE TO THE LAND IS TRANSFERRED.
- 4. THE CONTRACTOR SHALL BE RESPONSIBLE TO CONTROL DUST AND WIND EROSION THROUGHOUT THE LIFE OF HIS CONTRACT. DUST CONTROL SHALL INCLUDE, BUT IS NOT LIMITED TO, SPRINKLING OF WATER ON EXPOSED SOILS AND HAUL ROADS. CONTRACTOR SHALL CONTROL DUST TO PREVENT A HAZARD TO TRAFFIC ON ADJACENT ROADWAYS. 5. IF FINAL GRADING IS TO BE DELAYED FOR MORE THAN THIRTY (30) DAYS AFTER LAND DISTURBANCES CEASE, TEMPORARY VEGETATION OR MULCH SHALL BE USED TO STABILIZE SOILS. OUTSIDE OF THE GROWING SEASON, ONLY WOOD MULCH SHALL BE USED.
- 6. STRAW WATTLES SHALL BE USED ONLY AS A TEMPORARY MEASURE. WHERE CONTROL MEASURES WILL BE REQUIRED FOR LONGER THAN SIXTY (60) DAYS, FILTER FABRIC SHALL BE USED. 7. WHERE DEWATERING IS NECESSARY, THERE SHALL NOT BE A DISCHARGE DIRECTLY INTO WETLANDS OR WATERCOURSES. PROPER METHODS AND DEVICES SHALL BE UTILIZED TO THE EXTENT PERMITTED BY LAW, SUCH AS PUMPING WATER INTO A TEMPORARY SEDIMENTATION BASIN, PROVIDING SURGE PROTECTION AT THE INLET AND THE OUTLET OF PUMPS, FLOATING THE INTAKE OF THE PUMP, OR OTHER METHODS TO MINIMIZE AND RETAIN THE SUSPENDED SOLIDS. IF A PUMPING OPERATION IS CAUSING TURBIDITY PROBLEMS, SAID OPERATION SHALL CEASE UNTIL SUCH TIME AS FEASIBLE MEANS OF CONTROLLING TURBIDITY ARE DETERMINED AND IMPLEMENTED. THE CONTRACTOR MUST SUBMIT HIS DESIGN
- 8. INSPECTION A CERTIFIED SOIL SCIENTIST OR ENGINEER SHALL INSPECT ALL DISTURBED AREAS OF THE CONSTRUCTION ACTIVITY THAT HAVE NOT BEEN FINALLY STABILIZED, STRUCTURAL CONTROL MEASURES, AND LOCATIONS WHERE VEHICLES ENTER OR EXIT THE SITE AT LEAST ONCE EVERY WEEK AND WITHIN 24 HOURS OF THE END OF A STORM THAT IS 1.0 INCH OR GREATER. INSPECTION REPORTS SHALL BE SUBMITTED TO THE OWNER WEEKLY, AND TO THE INLAND WETLANDS AGENT AND THE PLANNING & ZONING COMMISSION MONTHLY. WHERE SITES HAVE BEEN FINALLY STABILIZED, SUCH INSPECTION SHALL BE CONDUCTED AT LEAST ONCE EVERY MONTH FOR THREE MONTHS. CONTROLS SHALL BE CLEANED, REPAIRED, AND OR REPLACED AS REQUIRED. ANY DAMAGED CONTROLS SHALL BE REPAIRED
- 9. PERFORM CONSTRUCTION SEQUENCING IN SUCH A MANNER TO CONTROL EROSION AND TO MINIMIZE THE TIME THAT EARTH MATERIALS ARE EXPOSED BEFORE THEY ARE COVERED, SEEDED, OR OTHERWISE STABILIZED.


ALONG WITH THE LOCATIONS OF THE BASIN TO THE TOWN PRIOR TO CONSTRUCTION.




NOTES:

1. INSPECT INLET PROTECTION WEEKLY AND AFTER EACH SIGNIFICANT RAIN EVENT. REMOVE ACCUMULATED SEDIMENT WHEN SILT SACK BECOMES MORE THAN 1/4 FULL.







ASPAHLT CURB SCALE: NOT TO SCALE




CONSTRUCTION ENTRANCE SCALE: NOT TO SCALE




1.) INSTALL SILT FENCE & WOOD STAKES AS RECOMMENDED BY MANUFACTURER. 2.) SYNTHETIC FILTER FABRIC SHALL BE A PERVIOUS SHEET OF PROPYLENE,




CONCRETE RETAINING WALL SCALE: NOT TO SCALE





1. MAXIMUM SLOPE SHALL BE 2:1.
2. TEMPORARILY STABILIZE STOCKPILES THAT WILL REMAIN INACTIVE FOR 7 DAYS OR MORE WITH TEMPORARY VEGETATION, WOODCHIP MULCH, STUMP GRINDINGS, OR JUTE NETS. REFER TO EROSION CONTROL NOTES ON SHEET GI-002 FOR ADDITIONAL STABILIZATION 3. DO NOT STOCKPILE WITHIN THE 100-FOOT BUFFER OF A WETLAND RESOURCE AREA.

STOCKPILE AREA SCALE: NOT TO SCALE



EXTERIOR CONCRETE NOTES: 12. ALL CONCRETE TO BE POURED WITH A MAXIMUM 4" 1. ALL WORK TO BE PERFORMED IN ACCORDANCE WITH THE MASSACHUSETTS STATE BUILDING CODE 8TH EDITION AND ALL LOCAL REQUIREMENTS. OR ABOVE MID DEPTH OF THE FLOOR SLAB UNLESS DIMENSIONS AND CONDITIONS SHALL BE VERIFIED IN TOP AND BOTTOM REINFORCEMENT IS SPECIFIED. FIELD PRIOR TO THE COMMENCEMENT OF WORK. 3. ALL CONCRETE SHALL HAVE A DESIGN STRENGTH CHAIRS OR BOLSTERS ONLY. OF 4000 PSI AT 28 DAYS, UNLESS OTHERWISE NOTED. 60 EXCEPT WHERE FIELD BENDING IS REQUIRED, GRADE

WELDED WIRE MESH SHALL BE ASTM A185. ALL FOLLOWS: WELDED WIRE MESH SHALL BE IN SHEET FORM. PROVIDE SAW CUT EXPANSION/CONTROL JOINTS AT AREAS NOTED. ALL SAW CUT EXPÁNSION JOINTS SHALL A MAXIMUM OF 1/3 OF THE SLAB THICKNESS. JOINTS TO POURING ADJACENT SLAB. MUST BE CUT WITHIN 24 HOURS OF CONCRETE PLACEMENT.

7. JOINTS MUST BE SPACED IN ACCORDANCE WITH ACI-318 AND THE FOLLOWING RECOMMENDATIONS: 4" THICK SLAB-15'X15' < 250 SQ FT 5" THICK SLAB-18'X18' < 325 SQ FT 6" THICK SLAB-20'X20' < 400 SQ FT 8" THICK SLAB-25'X25' < 500 SQ FT 8. ALL CONCRETE SHALL BE MIXED AND PLACED IN ACCORDANCE WITH THE ACI "BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE",

O. CONCRETE CONTRACTOR SHALL INSTALL CHASES THROUGH THE FOUNDATION WALLS AS DIRECTED BY THE GENERAL CONTRACTOR. 10. EXTERIOR CONCRETE SLABS TO HAVE A LIGHT BROOM FINISH. CONCRETE SLABS TO RECEIVE (1) COAT OF CLEAR SEALER/HARDENER EXCEPT AS NOTED.


11. ALL REINFORCING BARS TO HAVE MINIMUM 2"

SHEETS ARE TO BE USED IN ALL WELDED WIRE MESH APPLICATIONS. WELDED WIRE MESH TO BE PLACED WITH 14. POURING CONCRETE FLOORS IN A CHECKERBOARD REINFORCING RODS SHALL BE ASTM A615, GRADE PATTERN IS NOT APPROVED OR RECOMMENDED BY ACI. 15. SEPARATE POURS MUST HAVE SMOOTH DOWELS (WRAPPED OR GREASED). DOWEL SIZES SHALL BE AS 4" THICK SLAB 1/2"X12" LONG 18" O.C. 5" THICK SLAB 1/2"x12" LONG 18" O.C. 6" THICK SLAB 3/4"x16" LONG 18" O.C. BE A MINIMUM OF 1/4 OF THE SLAB THICKNESS AND BOND BREAKER COMPOUND TO BE PAINTED ON PRIOR 16. ENGINEER TO APPROVE SUBGRADES PRIOR TO SLAB 17. CONTROL JOINTS AROUND ALL SLAB PENETRATIONS SHOULD BE SAWCUT THE FULL DEPTH OF THE SLAB OR BE DONE AS A CONSTRUCTION JOINT (POURED SEPARATELY). 18. ALL JOINTS SHALL BE FILLED AND SEALED.

13. FLOOR SLAB REINFORCING MUST BE LOCATED AT

CONCRETE UTILITY PAD SCALE: NOT TO SCALE





FUSS&O'NEILI 0 MAIN STREET, SUITE 400 fando.com

617. 617. 617. 617. 781. \vdash \vdash \vdash \vdash \vdash \vdash

04.28.2023 100% SD Redesign Set 07.12.2023

C6.0

EMERGENCY SPILLWAY - PLAN VIEW

EMERGENCY SPILLWAY WITH REINFORCEMENT MATTING

MASSACHUSETTS 2' SQ. OPENING FRAME & GRATE, LEBARON LF244 OR APPROVED EQUAL. COVER (TYP.) _DRAIN PIPE AS SHOWN AND SPECIFIED ON THE PLANS PROVIDE "V" OPENINGS FOR PIPES MIN. 0.12 SQ. IN. STEEL PER VERTICAL FOOT IN ACCORDANCE TO CATCH BASIN AASHTO M199 (SEE DETAIL)

FUSS&O'NEILL

550 MAIN STREET, SUITE 400 PRINGFIELD, MA 01103 13.452.0445 ww.fando.com

.8960 .6060 .4675 .1200 .4502

617.876.8 617.357.0 617.282. 617.868. 617.354.

 \vdash \vdash \vdash \vdash \vdash \vdash

PRECAST CONCRETE CATCH BASIN SCALE: NOT TO SCALE


PAVEMENT | GRASS -FINISHED GRADE PAVEMENT TOPSOIL BASE I.D. + 2' STORM SEWER MARKING TAPE 18" MIN. ABOVE PIPE CROWN _ 3' MINIMUM FINAL BACKFILL - GRANULAR FILL, DEPTH VARIES COMPACT IN 6" LIFTS SEE PLAN /-INITIAL BACKFILL - GRANULAR FILL, COMPACT IN 6" LIFTS MIN. BEDDING - 3/4" CRUSHED STONE, COMPACT IN 6" LIFTS. ADDITIONAL 3/4" CRUSHED STONE BEDDING WHERE SUBGRADE IS UNSUITABLE MATERIAL OR ROCK

BASE TO BE PLACED ON SUITABLE UNDISTURBED MATERIAL

OR GRAVEL BORROW BASE

SCALE: NOT TO SCALE

DRAINAGE MAHNOLE



SECTION A - FRONT ELEVATION

REINFORCEMENT MATTING

(OR APPROVED EQUAL)


CURLEX ENFORCER- NATURAL ASPEN COLOR

INSTALL PER MANUFACTURER SPECIFICATIONS


TERMINAL CLEAN-OUT SCALE: NOT TO SCALE

(REFER TO LANDSCAPE


PLANS FOR SEEDING)



12" YARD DRAIN



RIP RAP PROTECTION SCALE: NOT TO SCALE.



C6.1

Revision:


04.28.2023

100% SD Redesign Set 07.12.2023

NOT FOR CONSTRUCTION

— SURFACE TO BE APPROXIMATELY LEVEL 1' MIN. OVERLAP -2" ANGULAR CLEAN STONE -6" PVC PERFORATED SDR-35 SEE PLAN FOR SLOPE AND INVERT INFORMATION. PIPE DEPTH WITHIN DRIPEDGE VARIES NON-WOVEN FILTER FABRIC REQUIRED. -PIPE TO BE SET AT BOTTOM OF WRAP STONE, (MIRAFI 140N OR EQUAL) -STONE IF POSSIBLE. NOTE: SLOPE SHALL MATCH SURFACE STORMWATER DRAINAGE TRENCH UNDERDRAIN TRENCH SCALE: NOT TO SCALE SCALE: NOT TO SCALE ROOF LEADER -SCREEN-— SEE GRADING PLAN FOR FINAL FINISH GRADE ELEVATIONS 4" Ø PVC RISER-─1-1/2" DIA. CLEAN ROUND STONE DRIP EDGE - LANDSCAPE EDGING- MATERIAL PER OWNER -4" TOPSOIL, GRASS SEED AND STRAW MULCH AS NEEDED NON-WOVEN FILTER FABRIC REQUIRED. +4" SOLID PVC PIPE WRAP STONE, (MIRAFI ⊢3/4" WASHED STONE 140N OR EQUAL)— 1' FOR R.C.C.E. -4" PVC PERFORATED SDR-35, SEE PLAN FOR SLOPE AND INVERT INFORMATION. PIPE DEPTH WITHIN DRIPEDGE VARIES --- MIN. 2" CLEARANCE UNDER PIPE -RIP RAP PROTECTION REFER TO DETAIL NOTE: BOTTOM OF STONE TO FOLLOW PIPE ELEVATION. MAINTENANCE: FOLLOWING LEAF DROP THE DRIP EDGE AREA SHALL BE CLEARED OF DEBRIS AND VEGETATION. IF WATER DOES NOT DRAIN IN 24 HOURS DURING THE GROWING SEASON OR HAS ACCUMULATED SEDIMENT TO THE TOP OF ROUND STONE, REMOVE, WASH, AND REPLACE THE 6" SURFACE LAYER OF ROUND STONE. CONCRETE CULVERT FLARED END REFER TO DETAIL NOTE SEE PLANS, PIPE SIZE, AND INVERTS. SECTION A-A CONCRETE FLARED END WITH RIP RAP APRON STONE DRIP EDGE AND ROOF LEADER TIE-IN SCALE: NOT TO SCALE. SCALE: NOT TO SCALE SCALE: NOT TO SCALE

SCALE: NOT TO SCALE



NOTES 1. "W" SHALL BE 10 FEET OR THE WIDTH OF THE BOTTOM OF THE BASIN, WHICHEVER IS LESS.

BASIN OUTLET UNDERDRAIN

SCALE: NOT TO SCALE.

EL.=REFER TO PLANS

TRASH RACK AND OPENINGS -

BASE OF STRUCTURE SHALL -BE PLACED ON SUITABLE MATERIAL

OUTLET CONTROL STRUCTURE

(REFER TO DETAIL)

OUTLET PIPE-

-

PRECAST CONCRETE >

abababab

SCALE: NOT TO SCALE.

SHOWN FOR CLARITY

- CONCRETE BRICK AND

MORTAR AS NECESSARY

INV. EL.=REFER TO PLANS

INV. EL.=REFER TO PLANS

WELD BARS.

 \longrightarrow A

← W (SEE NOTE)

<u>PLAN</u>

4"BOTTOM OF BASIN

WITH SOCK

2" CRUSHED STONE

FILTER FABRIC

∠6" PERFORATED UNDERDRAIN

-

SECTION B-B

OUTLET PIPE -

NOTE

1. CONSTRUCT TRASH RACK OVER OPENINGS. #3 BARS
AT 6" O.C. WELD TO ANGLES 2"x2"x1/4" AND BOLT TO

2. FOR CONSTRUCTION THAT DO NOT HAVE AN ORIFICE

STRUCTURE USING 3/8" EXPANSION ANCHORS. TACK

AT THE LOWEST STORAGE ELEVATION, PROVIDE A 6"
PVC PIPE AND END CAP TO ALLOW BASIN TO BE
DRAINED MANUALLY.

SEE NOTE 1

SECTION A-A


6" PERFORATED -

UNDERDRAIN WITH SOCK

2" CRUSHED STONE TWRAPPED IN FILTER FABRIC

OUTLET CONTROL STRUCTURE (OCS)

- PRECAST CONCRETE RISER





FRONT ELEVATION

SEE GRADING PLAN

OUTLET PIPE -

SIDE ELEVATION







- PARGE VISIBLE CONCRETE SURFACES


-SET RIP RAP 6" BELOW INVERT

- MODIFIED RIP RAP

GRAB STRENGTH

NON-WOVEN STABILIZATION FABRIC W/MIN 160 LBS.

OF LOWEST OPENING



MASSACHUSETTS 2' SQ. OPENING FRAME & GRATE, FRAME & GRATE CONFORMING TO MASSACHUSETTS DOT SPECIFICATIONS

-TRASH RACK SHOWN FOR CLARITY

INV. EL.=REFER TO PLANS

EL.=REFER TO PLANS

SEE NOTE 1

INV. EL.=REFER TO PLANS

POUR CONCRETE INVERT AT BOTTOM OF STRUCTURE TO

DRAIN TO OUTLET PIPE



C6.2

NOT FOR CONSTRUCTION


Revision:

04.28.2023

100% SD Redesign Set 07.12.2023

FUSS&O'NEILL

617.8 617.8 617.8 617.8 617.8 \vdash \vdash \vdash \vdash \vdash \vdash




STANDARD MANHOLE



BRICK MASONRY OR CLASS A CONCRETE

NOTE:

PUBLIC WORKS.




SECTION A-A


DETAIL SHOWN FOR ILLUSTRATIVE PURPOSES ONLY. INSTALLATION OF

SANITARY SEWERS SHALL BE COORDINATED WITH THE CITY/TOWN

TYPICAL WATER SERVICE CURB BOX SCALE: NOT TO SCALE




WATER MAIN TRENCH SCALE: NOT TO SCALE




- IF 18" VERTICAL SEPARATION CAN NOT BE ACHIEVED AT LOCATIONS OF WATER MAIN & SEWER CROSSINGS, CONTRACTOR SHALL CONSTRUCT EITHER OF THE FOLLOWING OPTIONS:
- 1. CONSTRUCT SANITARY SEWER OF PVC PRESSURE PIPE MATERIAL 10' ON EACH SIDE OF THE WATER MAIN/STORM SEWER AND TEST PROPOSE SANITARY SEWER AT 150 PSI PRESSURE. 2. ENCASE SEWER PIPE IN CONCRETE, 4' DISTANCE ON EACH SIDE OF WATER MAIN/ STORM SEWER CROSSING. CONCRETE ENCASEMENT SHALL BE MINIMUM 6" ALL AROUND PROPOSED SEWER PIPE.

WATER/SEWER SEPARATION REQUIREMENTS


SCALE: NOT TO SCALE




8 LOW PRESSURE SEWER TRENCH
SCALE: NOT TO SCALE




SANITARY SEWER TRENCH



PIPE LAYOUT @ 90° TURNS SCALE: NOT TO SCALE



WATER MAIN JOINT RESTRAINT SCALE: NOT TO SCALE





NOT FOR CONSTRUCTION



FUSS&O'NEILL

1550 MAIN STREET, SUITE 400 SPRINGFIELD, MA 01103 413.452.0445 www.fando.com

.8960 .6060 .4675 .1200 .4502

876. 357. 282. 868. 354. 749.


617.8 617.8 617.8 617.8 617.8

 \vdash \vdash \vdash \vdash \vdash \vdash

04.28.2023

100% SD Redesign Set 07.12.2023

C6.3









T. 617.876.8960 T. 617.357.6060 T. 617.282.4675 T. 617.868.1200 T. 617.354.4502 T. 781.749.7272

NEW ENGLAND WILDFLOWER SEED MIX- 36,572 sf
Asclepias tuberosa / Butterfly Milkweed
Elymus canadensis / Canada Wild Rye
Elymus virginicus / Virginia Wild Rye

Eupatorium fistulosum / Hollow Joe Pye Weed

Festuca rubra / Red Fescue
Sorghastrum nutans / Indian Grass

NEW ENGLAND RESTORATION SEED MIX- 8,114 sf
Agrostis perennans / Autumn Bentgrass
Andropogon gerardii / Big Bluestem
Aster novae-angliae / New England Aster
Bidens cernua / Nodding Beggartick
Elymus riparius / Riverbank Rye
Eupatorium fistulosum / Hollow Joe Pye Weed
Eupatorium perfoliatum / Common Boneset
Festuca rubra / Red Fescue
Juncus effusus / Soft Rush
Panicum virgatum / Switch Grass
Schizachyrium scoparium / Little Bluestem
Scirpus cyperinus / Wool Grass

NEW ENGLAND NATIVE WARM SEASON GRASS SEED MIX- 6,924 sf Andropogon gerardii / Big Bluestem

Andropogon gerardii / Big Bluestem
Andropogon scoparius / Little Bluestem
Elymus virginicus / Virginia Wild Rye
Festuca rubra / Red Fescue
Panicum virgatum / Switch Grass
Sorghastrum nutans / Indian Grass

NATIVE HERBACEOUS PERRENNIAL MIX- 2,719 sf Agastache pallidiflora / Giant Hyssop

Verbena hastata / Blue Vervain

Echinacea purpurea / Coneflower

Monarda didyma / Bee Balm

Eupatorium maculatum / Joe Pye Weed

Symphyotrichum puniceum / Swamp Aster

WOODLAND MIX- 1,007 sf
Anemone canadensis / Canadian Anemone
Dennstaedtia punctiloba / Hayscented Fern
Polystichum acrostichoides / Christmas Fern

QTY SIZE SPACING

465 1 Gal 18" oc
465 1 Gal 18" oc
465 1 Gal 18" oc

1,255

1,255 1,255

1,255 1,255 1 Qt

1 Qt

1 Gal

1 Qt

1 Gal

18" oc

18" oc

18" oc

CODE	BOTANICAL / COMMON NAME	CONT	CAL	SIZE	QTY	REMARKS
TREES						
AR	Acer rubrum / Red Maple	B & B	2.5"-3" Cal		12	
AS2	Amelanchier alnifolia / Serviceberry	B & B		5`-6` H	9	
BW	Betula populifolia `Whitespire` / Whitespire Gray Birch	B & B	2.5"-3" Cal		3	
СМ	Cornus mas / Cornelian Cherry	B & B		5`-6` H	2	
HV	Hamamelis virginiana / Common Witch Hazel	B & B		5`-6` H	7	
NS	Nyssa sylvatica / Tupelo	B & B	2.5"-3" Cal		7	
OA	Oxydendrum arboreum / Sourwood Tree	B & B	2.5"-3" Cal		3	
PG	Picea glauca / White Spruce	8-10` HT.	2.5"-3" Cal		3	
QB	Quercus bicolor / Swamp White Oak	B & B	2.5"-3" Cal		5	
SB2	Salix nigra / Black Willow	B & B	2.5"-3" Cal		2	
SA	Sassafras albidum / Sassafras	B & B	2.5"-3" Cal		8	
TC	Tsuga canadensis / Eastern Hemlock	8-10` HT.	2.5"-3" Cal		4	
CODE	BOTANICAL / COMMON NAME	CONT	SIZE		QTY	REMARKS
SHRUB	9		•	•		
CI CI	Celphanthus occidentalis / Buttonbush	B & B			22	
CA	Clethra alnifolia / Summersweet Clethra	B & B	5`-6` H		15	
HP	Hydrangea paniculata / Panicle Hydrangea	B & B			11	
IV	Ilex verticillata `Red Sprite` / Red Sprite Winterberry	B & B	3, H		24	1 MALE TO 4 FEMALE
LB	Lindera benzoin / Spicebush	B & B			19	
RM	Rhododendron maximum / Rosebay Rhododendron	B & B	5`-6` H		9	
	1	_		1		



.8960 .6060 .4675 .1200 .4502

617.876.8 617.357.0 617.282. 617.868. 617.354.

 \vdash \vdash \vdash \vdash \vdash \vdash \vdash

66 Leverett Road


LAN

1: GT,GL

L3.0

I N .: ON ISO






 \vdash \vdash \vdash \vdash \vdash \vdash \vdash

. 617.876.8960 . 617.357.6060 . 617.282.4675 . 617.868.1200 . 617.354.4502

SHUTESBURY PL 66 Leverett Road

Revision: 04.28.2023 100% SD Redesign Set 07.12.2023 100% DD Set 12.11.2023 NOI Submission 12.22.2023

LD GT, GL 2304



#4@18"OC, 3"CLR MIN

AGGREGATE BASE COURSE,


REFER TO MANUFACTURER INSTALLATION

COMPACTED OR UNDISTURBED SUBGRADE

FROM EDGE OF CONC

SPECIFICATIONS

BIKE RACK



SITE SALVAGED BOULDER

TAP SALVAGED STEEL PLATE $-\frac{1}{2}$ "x1-1/4"Ø SS SPACER

½" POLYCARBONATE PANEL, UV

POLYCARBONATE

- ½" TH. SALVAGED STEEL PLATE

TH. SALVAGED STEEL GUSSET PLATE, STITCH WELD TO PLATE

ANCHORS, SEE STRUCTURAL DWGS

DEPTH, SEE STRUCTURAL DWGS

(12) ½"Ø SS BUTTON HEAD BOLT, TAMPER PROOF, 12"O.C. 1-1/2" CLEAR, TYP.

 DIGITAL PRINT PROCESS ON PRESSURE SENSITIVE CLEAR VINYL WITH LAMINATE COAT, ADHERE TO BACK SIDE OF POLYCARBONATE, LEAVE $\frac{1}{16}$ " SPACE BETWEEN VINYL SHEET AND EDGE OF

1 TH. SALVAGED STEEL GUSSET PLATE, STITCH WELD TO

¹₄" POLYCARBONATE PANEL, UV

POLYCARBONATE

— ½" TH. SALVAGED STEEL PLATE

REINFORCED CONC FOOTING, MIN 3'-0" DEPTH, SEE STRUCTURAL DWGS

NOTE: DIGITAL ART FOR ALUMINUM

 $\frac{3}{4}$ " POST BOLT

GALVANIZED NAIL

- 6" X 8" X 1'-2 " WOOD CR

REINFORCED CONC FOOTING, MIN 3'-0"


COMPACTED OR UNDISTURBED SUBGRADE


BACKFRONT

(12) 1_4 % SS BUTTON HEAD BOLT, TAMPER PROOF, 12"0.C. 1-1/2" CLEAR, TYP.

DIGITAL PRINT PROCESS ON PRESSURE SENSITIVE CLEAR VINYL WITH LAMINATE COAT, ADHERE TO

BACK SIDE OF POLYCARBONATE, LEAVE $\frac{1}{16}$ " SPACE BETWEEN VINYL SHEET AND EDGE OF





04.28.2023

12.11.2023